

# TOP GLOVE

TOP QUALITY, TOP EFFICIENCY

THE WORLD'S LARGEST MANUFACTURER OF GLOVES

## NITRILE GLOVE

POWDERED & POWDER-FREE



### Functional Benefits:

- Protection from unwanted or dangerous substances
- Beaded cuff makes donning easy and helps prevent roll back
- Superior strength with better puncture resistance
- Full textured enhances wet and dry grip
- Thinner gauger improves tactile sensitivity
- Custom design enhances comfort and fit
- Provide an alternative solution for individuals who are allergic to natural rubber latex



NITRILE GLOVE

# NITRILE GLOVE

POWDERED & POWDER-FREE

## Quality Standards

- Conforms to ASTM D6319 and EN455 Standards
- Manufactured under QSR (GMP), ISO 9001:2015 and ISO 13485:2016 Quality Management System

## Glove Sizes

- Extra-Small, Small, Medium, Large, Extra-Large
- Size of gloves shall be marked in the check box on the shipping carton with black ink

## Product Specifications

- Type** : Powdered & Powder-Free, Non-sterile
- Material** : 100% Synthetic Nitrile Latex
- Colour** : Blue, White, Green, Pink, Light Purple, Black, Red
- Design & Features** : **Powdered:**  
Ambidextrous, finger textured or palm textured surface, beaded cuff, USP grade absorbable cornstarch
- Powder-Free:**  
Polymer coated or online single chlorinated, offline double chlorinated, ambidextrous, finger textured or palm textured surface, beaded cuff
- Storage** : The gloves shall maintain their properties when stored in a dry condition. Avoid direct sunlight
- Shelf-life** : 5 years from the date of manufacturing



## Physical Dimensions

Dimensions	Standards		
	Top Glove	ASTM D3578	EN 455
<b>Length (mm)</b>	Min 230, Min 240, 300 ± 10	Min 220 (XS, S) Min 230 (M, L, XL)	Min 240
<b>Palm Width (mm)</b>			
• XS	76 ± 3	70 ± 10	≤ 80
• S	84 ± 3	80 ± 10	80 ± 10
• M	94 ± 3	95 ± 10	95 ± 10
• L	105 ± 3	110 ± 10	110 ± 10
• XL	113 ± 3	120 ± 10	≥ 110
<b>Thickness : Single Wall (mm)</b>			
• Finger	Min 0.05	Min 0.05	N/A
• Palm	Min 0.05	Min 0.05	N/A

## Physical Properties

Property	ASTM D6319	EN 455
<b>Tensile Strength (MPa)</b>		
• Before Aging	Min 14	N/A
• After Aging	Min 14	N/A
<b>Elongation at Break (%)</b>		
• Before Aging	Min 500	N/A
• After Aging	Min 400	N/A
<b>Median Force at Break (N)</b>		
• Before Aging	N/A	Min 6
• After Aging	N/A	Min 6

### International Quality Certificate Awarded:



If you have any enquiries on our products, please contact :

## TOP GLOVE SALES & CORPORATE OFFICE

Level 21, Top Glove Tower,  
16, Persiaran Setia Dagang,  
Setia Alam, Seksyen U13,  
40170 Shah Alam,  
Selangor D.E., Malaysia.

Tel : +603-3362 3098  
Fax : +603-3362 5096 (Sales)  
Email : sales@topglove.com.my

 <https://www.facebook.com/topglovecorp>

 [www.topglove.com](http://www.topglove.com)